

[54] **ELECTROPHORETIC DISPLAY  
COMPOSITION**

[75] Inventor: **Anne A. Chiang**, Cupertino, Calif.  
[73] Assignee: **Xerox Corporation**, Stamford, Conn.  
[21] Appl. No.: **77,416**

[22] Filed: **Sep. 20, 1979**

[51] Int. Cl.<sup>3</sup> ..... **C25D 13/00; G02F 1/01**  
[52] U.S. Cl. .... **204/299 R; 252/62.51;**  
**252/62.53; 350/355; 350/362**  
[58] Field of Search ..... **204/180 R, 299 R, 299 PE,**  
**204/181 PE, 181 R; 96/112, 1.5, 1 PE; 355/3, 3**  
**P, 4, 5; 350/160 R, 355, 345, 362; 324/324 EC;**  
**340/173 CH; 252/62.1, 62.51-62.54; 117/37**  
**LE**

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

3,058,914	10/1962	Metcalf et al. ....	252/62.1
3,627,682	12/1971	Hall, Jr. et al. ....	252/62.54
3,640,751	2/1972	Kazuhiko et al. ....	117/37 LE
3,668,106	6/1972	Ota .....	204/299
4,093,534	6/1978	Carter et al. ....	204/299 R X

*Primary Examiner*—F. Edmundson

[57] **ABSTRACT**

A suspension for electrophoretic display systems, such as the display systems shown in U.S. Pat. No. 3,668,106, is described. The particles in the suspension are coated with a highly fluorinated polymeric material, which acts as a dispersant. Preferably, the suspension also includes a charge control agent.

**3 Claims, No Drawings**